

Hydraulic // 0...1000 bar



P700.3 Basic



P1000.2 Solid

Your advantages

Type	P700.3 / P1000.2
	• Testing, adjustment and calibration of all types of pressure gauges • Precise adjustment thanks to ultra fine thread pitch and large volume control valve • High pressure generation with minimum effort • Large calibration volume (300 ml)

Technical data

Type	P700.3		P1000.2
Pressure range	0...700 bar		0...1000 bar
Pressure medium	Demineralized water or hydraulic oil		
Connections			
Reference pressure gauge	G¼		
Test sample	G¼ with quick coupling and pressure hose (1 m)		G¼ with quick coupling and high pressure hose (1 m)
Basic			
Dimensions	Approx. 255 x 225 x 85 mm		
Weight	Approx. 1,7 kg		Approx. 1,9 kg
Solid			
Dimensions (case)	Approx. 450 x 370 x 125 mm		
Weight	Approx. 4,8 kg		Approx. 5 kg
+ Adapter kit	Stainless steel, G½, G¼, G¾, G½, ⅛ NPT, ¼ NPT, ½ NPT, M12 x 1.5, M20 x 1.5, G½, G¼		
+ Seal kit	PA flat gaskets and O-rings		

Order code

Type	Version	Order number
P700.3	Basic	EPPM700EBL0000
	Solid (incl. case and adapter)	EPPM7000BL0000
P1000.2	Basic	EPPM1K0EBL0002
	Solid (incl. case and adapter)	EPPM1K00BL0002