



SEMI-COMMERCIAL WASHER

FW60

6 KG

SEMI-COMMERCIAL DRYER

FD112-FDC112-FDHP112

6 KG

FEATURES

WASHER-EXTRACTORS

- White cabinet
- Stainless steel drum and tub
- Easy to use timer
- Mop and medical programs
- Soap hopper at the front
- Matching dryer available – space saving when placed on top

DRYERS

- White cabinet
- Stainless steel drum and tub
- Large door opening (Ø 45 cm)

OPTIONS

WASHER-EXTRACTORS

- External coin meter
- Drain valve
- Liquid soap pumps
- Marine voltages available

DRYERS

- External coin meter
- Condens unit (FDC112)
- Heat pump heating (FDHP112)
- Marine voltages available



FW60



FD112

	FW60
DRUM	
CAPACITY (KG)	6
CYLINDER VOLUME (L)	60
DIAMETER (MM)	480
DRUM SPEED	
EXTRACTION SPEED (RPM)	1600
G-FACTOR	690
CONNECTIONS	
ELECTRIC (KW)	200V/50-60Hz/1 230V/50-60Hz/1 400-415V/50-60Hz/3+N 400-440V/60Hz/3
WATER (IN)	3/4"
CIRCUIT BREAKER	230V-10A/ 400V-16A
DRAIN	
DRAIN TYPE	Pump standard Drain valve optional
TRANSPORT DATA	
GROSS WEIGHT (KG)	78
NET WEIGHT (KG)	76
DIMENSIONS H X W X D (MM)	850 X 595 X 585
PACKING DIMENSIONS H X W X D (MM)	920 X 640 X 660

	FD112 vented dryer	FDC112 condense dryer	FDHP112 heat pump dryer
DRUM			
CAPACITY (KG)	6	6	6
CYLINDER VOLUME (L)	112	112	112
DIAMETER (MM)	571	571	571
HEATING			
ELECTRIC (KW)	200V/50-60Hz/1 230V/50-60Hz/1 400-415V/50-60Hz/3+N 400-440V/60Hz/3	200V/50-60Hz/1 230V/50-60Hz/1 400-415V/50-60Hz/3+N 400-440V/60Hz/3	200V/50-60Hz/1 230V/50-60Hz/1 400-415V/50-60Hz/3+N 400-440V/60Hz/3
CIRCUIT BREAKER	230V-10A/ 400V-16A	230V-10A/ 400V-16A	230V-10A/ 400V-16A
AIRFLOW (M³/H)	123	123	123
AIR EVACUATION	100	-	-
TRANSPORT DATA			
GROSS WEIGHT (KG)	42	46	54
NET WEIGHT (KG)	40	44	52
DIMENSIONS H X W X D (MM)	850 X 595 X 585	850 X 595 X 585	850 X 595 X 585
PACKING DIMENSIONS H X W X D (MM)	920 X 640 X 660	920 X 640 X 660	920 X 640 X 660