



DECKMA
HAMBURG

15ppm Bilge Alarm OMD-2008 EV

According to regulations of IMO Resolution MEPC. 107(49)
U.S. Coast Guard approved



We help to protect the Environment



Specification OMD-2008 EV (EV=Electric Valve)

Range:	0 – 30 ppm, Trend indication 50 ppm
Accuracy:	According IMO MEPC. 107(49)
Linearity:	Up to 30 ppm better than $\pm 2\%$
Display:	Yellow Graphic Display
Power Supply:	24 V – 240 V AC or DC, Automatic Voltage selection
Consumption:	< 10 VA
Alarm Points 1 + 2:	Adjustable between 1 - 15 ppm (Works adjustment 15 ppm)
Alarm 1 Operating Delay: (for annunciation purpose)	Adjustable between 1 – 540 sec. (Works adjustment 2 sec)
Alarm 2 Operating Delay: (for control purposes)	Adjustable between 1 – 10 sec. (Works adjustment 10 sec)
System Fault Alarm:	Red LED
Alarm Contact Rating:	Potential free 1 pole change over contacts, 3 A / 240 V
Alarm Indication:	Red LEDs
Output Signal:	0 – 20 mA or 4 – 20 mA selectable active current loop, ext. Load < 150 Ω
Clean Water Pressure:	0-6 bar
Sample Water Pressure:	0,1 – 6 bar
Sample Flow:	Approx. 0,1 - 3 l/min depend. on pressure
Ambient Temperature:	+ 1 to + 55° C
Sample Water Temperature:	+ 1 to + 65° C
Roll:	Up to 45°
Size (over all):	360 mm W x 240 mm H x 100 mm D
Distance (Computer Unit to Measuring Cell):	Up to 0.5m Option: up to 5m upon request
Degree of Protection:	IP 65
Weight:	5,4 kg
Pipe Connections:	R ¼" Female

Technical specifications are subject to change without notification

Contacts / Enquiries:

Agent:

DECKMA HAMBURG GmbH

Phone: +49 (0) 40 54 88 76 - 0
Fax: +49 (0) 40 54 88 76 - 10
e-mail: post@deckma.com
Internet: www.deckma.com
Address: Kieler Strasse 316
22525 Hamburg – Germany